VaporPro™ Product Data Sheet

10 MIL CLASS A VAPOR BARRIER

MANUFACTURER

Revolution Commercial Solutions (TX), LLC 3328 Executive Blvd Mesquite, TX 75149

PRODUCT DESCRIPTION

VaporPro™ is a high-performance polyethylene film designed for use as a vapor retarder under concrete slabs. This film is manufactured in the United States of America using high quality prime, virgin resins. VaporPro is designed as a low permeance, high strength, and high puncture resistant film that meets and exceeds the ASTM E1745-17 requirements for a Class A vapor retarder.



TECHNICAL DATA

Technical Property		Test Method	10 Mil Results	Unit
Color			Green	
Thickness, Nominal			10	mils
Roll Dimensions			14 x 210	feet
Surface Area			2,940	feet ²
Roll Weight			141	lbs
Classification		ASTM E1745-17	Class A, B, & C	
Puncture Resistance		ASTM D1709	2,645	grams
Tensile Strength		ASTM D882	55	lbf/in
6	ofter wetting, drying, soaking ofter heat conditioning ofter low temp conditioning ofter soil organism exposure	ASTM F1249 ASTM E154 Section 7 Section 8 Section 11 Section 12 Section 13	0.0077 0.0033 0.0029 0.0037 0.0051	perms
Methane Gas Permeation		ISO 2782-1	444 GTR, mL(STP)/(m ^{2*} day)	
Radon Diffusion Coefficient		K124/02/95	$(2.76 \pm 0.29) \times 10^{-12} (\text{m}^2\text{s}^{-1})$	

Note: perms = grains/(ft2*hr*in-Hg)

INSTALLATION

VaporPro™ vapor barrier is to be installed by following the guidelines of ASTM E1643. Unroll the vapor barrier over a sand, tamped earth, or aggregate base. Ensure that the seams of vapor barrier overlap a minimum of six inches and are sealed using a low permeance, high adhesion seam tape. All penetrations of the vapor barrier film must be sealed.

LIFETIME WARRANTY

Revolution offers a lifetime warranty on VaporPro™ to meet the published specifications as well as to be free of defects in product materials and workmanship at the time of shipment. Revolution does not offer any warranties with regards to the merchantability or fitness of products for a particular use. Please contact Revolution for more information surrounding the lifetime warranty of VaporPro™ solutions.

SALES & TECHNICAL SERVICES

Sales and technical information can be obtained by contacting Revolution.

vaporpro@revolutioncompany.com 972.216.3331

